



designed to be different

**Product specification Art 3-01 / Style 4-01 \*)**

Model name	Art 3-01 / Style 4-01
Description	Wall heater with enamelled sheet metal heat exchanger
Purpose	Local heating
Type of appliance	Wall mounted heater
Type of combustion	Closed combustion (C <sub>11</sub> )
Gas	Natural gas. Propane with conversion kit.
Flame picture	No visible flame
Sizes	Casing Art 3-01 WxHxD = 545x503x232mm excl. flue spigot Casing Style 4-01 WxHxD = 615x571x234mm
Flue spigot	Ø160/84mm, back side. Height heart flue spigot: min. 310mm
Removal of combustion products	Natural draught
Control	Thermostatic modulating from setting 1 to 6, based on capillary tube.
Operation	Manually operated
Ignition	Piezo igniter
Gas connection	3/8" male
Safety	Closed combustion
Accessories and options	Eco control pack; for room temperature control through capillary tube by remote control (radio frequency), setting 1 to 6 possible. Including 24 hour program and week program. If there is no motor movement in three consecutive days, flue fire will automatically be turned down to lowest setting. After in total 5 days flue fire will shut off. Possibility to connect a window switch and / or presence sensing device.
Weight	Art 3-01: 16kg Style 4-01: 20kg
Special features	Can be used for G25.3 (NL), G25 (25mbar) and G20 (20mbar) without conversion.
CE-ID (PIN)	0063AR3775

\*) Consult installation manual for the details.

<b>Gas type:</b>	<b>G25</b>	<b>G25.3</b>	<b>G20</b>	<b>G31</b>	<b>Unit</b>
Maximum output	2,8	2,8	3,0	3,4	kW
Minimum output	0,9	0,9	0,9	1,0	kW
Input rating (Hs)	3,7	3,7	3,9	4,3	kW
Gas usage high	396	396	370	158	l/h
Gas usage low	133	133	121	52	l/h
Efficiency class	1	1	1	1	
NOx class	5	5	4	5	
Efficiency (system efficiency)	83,0	83,0	84,1	85,9	%
Energy Efficiency Index	83	83	84	86	
Energy Efficiency Class	<b>B</b>	<b>B</b>	<b>B</b>	<b>B</b>	

**Modifications review**

Date	Nature of modification
01-10-2017	New specification