



Special features	<ul style="list-style-type: none"> <li>- Line burner</li> <li>- Chips (two colours: grey and dark grey)</li> <li>- Excluding: control hatch</li> <li>- Adjustable legs. Extension legs optional.</li> <li>- Wall mounting brackets</li> <li>- The appliance can be hung on the wall (in the suspension strip). In that case extension legs are not needed.</li> <li>- Maximum distance control hatch to the side of the appliance:               <ul style="list-style-type: none"> <li>- left           80cm</li> <li>- right         70cm</li> </ul> </li> </ul>
CE-ID (PIN)	0063CQ3296

**\*) Consult installation manual for the details.**

<b>Gas type:</b>	<b>G25</b>	<b>G25.3</b>	<b>G20</b>	<b>G31</b>	<b>Unit</b>
Maximum output	7,1	7,1	7,5	7,0	kW
Minimum output	2,6	2,6	2,8	3,5	kW
Input rating (Hs)	9,1	9,1	9,7	8,6	kW
Gas usage high	975	975	912	316	l/h
Gas usage low	381	381	364	174	l/h
Fluegas Temperature (12m vertical or testflue EN613)	300	300	309	320	°C
CO2-max (12m vertical or testflue EN613)	5,00	5,00	5,00	4,95	%
Fluegas flow (12m vertical or testflue EN613)	6,07	6,07	6,60	6,91	gr/sec
Min. draught required	5	5	5	5	Pa
Efficiency class (acc to EN613)	1	1	1	1	
NOx class (acc to EN613)	5	5	5	5	
Efficiency (system efficiency)	93,9	93,9	94,0	95,6	%
Energy Efficiency Index	94	94	94	96	
Energie Efficiency Class	<b>A</b>	<b>A</b>	<b>A</b>	<b>A</b>	

#### **Modification overview**

Date	Nature of modification
16-12-2015	New specification
26-10-2017	Update of gas technical specifications
22-08-2018	General update. PowerVent no longer possible.