



designed to be different

Product specification Maestro 75 RCH *)



Model name	Maestro 75 RCH			
Description	Balanced flue build in gas fire. Frontal fire view, minimal frame. Double burner system, top burners can be switched off (Dynamic Flame Burner®). Easily openable front window (Easy Release® glass window). High flame picture with relatively low in/output. Several interiors available. Anti-reflective glass (Clear View) optionally. Robust wood logs.			
Purpose	Balanced flue fire			
Type of appliance	Build in fire			
Type of combustion	Closed combustion C11/C31/C91, with Powervent: C12/C32.			
Gas	Natural gas G20, G25.3, G25 or propane G31. Conversion from natural gas to propane, v.v., not possible			
Flame picture	Yellow log fire			
Sizes	Engine: WxHxD = 981x1130 ... 1180x400mm (height including flue spigot) Build in plaster trim: WxH = 814x697mm Bottom of build in frame: min. 110mm			
Flue spigot	Ø200/130mm, top side in the middle			
Removal of combustion products	Natural draught. Powervent® possible.			
Flueing possibilities with wall terminal	gas	min. vertical	max. horizontal	notes
	natural gas	0.0m	0m	bend directly on appliance, wall terminal directly connected to bend: use stainless steel flue material
		>0.5m	6m	Wall terminal Ø200/130
		>0.8m	8m	Wall terminal Ø200/130
		≥0.5m	0m	Wall terminal Ø150/100; reduce just before bend
		≥0.8m	1m	Wall terminal Ø150/100; reduce just after bend
propane	As natural gas	As natural gas		
Removal of heat	Breast ventilation mandatory (>200cm ²)			
Control	RCH = Honeywell ESYS-02 system. Control options: manual or thermostatic. Clock program (week program) with 6 switch points per day.			
Operation	<ul style="list-style-type: none"> - Radiographic remote control 866MHz, battery operated (2x battery AA). Two way communication. Reading out of fault codes and fault history. Or: - Wireless via tablet (Android or iOS) + app and WIFI, or - Wired, with house management system 			
Ignition	Electronic ignition on main burner. No pilot burner.			
Electrical connection	230VAC with earth connection			
Gas connection	Ø15 fitting with compression nut (adapter supplied in carton box)			
Safety	<ul style="list-style-type: none"> - Ionisation detection. Separate ionisation electrode not only checks ignition, but also cross lighting of main burner. - Explosion hatches 			
Accessories and options	<ul style="list-style-type: none"> - PowerVent - Communication module (needed for external operation via tablet/app, smartphone or domotics) - Anti-reflective glass - Extension legs 			
Weight	Engine: 80kg			
Including	Control hatch, wood logs, glowing 'wool', 'ashes', remote control, batteries, socket wrench no 8 (window glass handle), connector 3/8" male/Ø15 compression nut, and mains wire + plug (EU and UK) L=150+150cm			



designed to be different

Special features	<ul style="list-style-type: none"> - The appliance can be operated with an app on tablet (Android or iOS) or smart phone. - Eco-Wave-technics (programmable flame height as function of the time) for lower gas consumption and more lively flames. - Triple vario-burner®-system, top two burners can be switched on/off separately, resulting in great modulation depth. - Top two burners (Dynamic flame burners®) are hidden in the wood logs, thus resulting in a very realistic flame picture. - Tilttable, bottom hinged, removable glass window (Easy Release door system®), to be opened with one hand movement, for easy cleaning of the glass. - 4-sided build in frame can be converted to a 3-sided build in frame by removing the bottom strip. A stone hearth (e.g.) can then continue till the glass. - Maximum distance control hatch to the side of the appliance: <ul style="list-style-type: none"> - left 75cm - right 65cm
CE-ID (PIN)	0063CQ3299

*) Consult installation manual for the details.

Gas type:	G25	G25.3	G20	G30	G31 (Q2-2019)	G31	Unit
Maximum output	8,6	8,6	9,0	8,9	7,4	7,9	kW
Minimum output	1,2	1,2	1,3	1,6	1,3	1,3	kW
Input rating (Hs)	11,4	11,4	12,0	12,0	10,3	11,2	kW
Gas usage high	1223	1223	1140	340	385	405	l/h
Gas usage low	209	209	218	69	79	81	l/h
Fluegas Temperature (12m vertical or testflue EN613)	328	328	332	323	303	318	°C
CO2 (12m vertical or testflue EN613)	4,00	4,00	4,20	5,44	4,65	4,25	%
Fluegas flow (12m vertical or testflue EN613)	9,51	9,51	9,72	9,03	8,82	10,47	gr/sec
Min. draught required	5	5	5	5	5	5	Pa
Efficiency class (acc to EN613)	1	1	1	1	1	1	
NOx class (acc to EN613)	4	4	4	5	5	5	
Efficiency (system efficiency)	91,3	91,3	89,0	91,1	90,5	89,5	%
Energy Efficiency Index	91	91	89	90	90	90	
Energie Efficiency Class	A	A	A	A	A	A	

Modifications review

Date	Nature of modification
15-10-2015	New specification
21-12-2015	Propane added
19-06-2017	Height now including flue spigot. NOx class added. Several other modifications.
26-10-2017	Update of gas technical specifications
11-01-2019	Update of gas technical specifications
23-04-2019	Type of combustion: for appliances with PowerVent C12/C32 added